



ADV Liquid Laminator

economical coating

1300 423 826

Finishing your prints does not have to be your bottle-neck

- Laminate up to 2.1m wide
- Very reliable and easy to use
- Affordable and economical
- Extends longevity of the graphic
- Production speed of 90m² p/hr
- Instant drying
- 12 month warranty



The ADV Liquid Laminator uses a special water-soluble liquid to spread over a wide range of solvent inkjet printed flexible materials such as banner vinyl, canvas and other similar media. Prints are dried instantly allowing for roll to roll operation.

The ADV Liquid Laminator produces a protective film over the graphic which increase the durability and longevity of the print.

The ADV Liquid Laminator is widely used in the post-production of outside/inside advertisement and vehicle graphics. The liquid film is formed directly on the media surface. The film thickness can be controlled by the operator and the liquid laminate is affixed firmly to the graphic.

Our ADV Liquid Laminator achieves a solid flexible coating through its precise application of the liquid and its drying and cooling system.

The price of our liquid film is lower than traditional flexible cold laminating film. In addition the liquid film application process is able to be conducted at a much higher speed. So laminating with our ADV Liquid Laminator can save you time and money while at the same time increasing the durability, longevity and general colour richness of your prints.

Max. Laminating Width	2100mm(83")
Laminating Speed	1-1.5m/min (40"-59")
Laminating Thickness	0.007-0.01mm(thickness adjustable)
Laminating Temperature	100-130 degree
Max.Heating Temperature	150 degree
Heating Power	8.4KW
Film Supply Mode	Magnetic suspension liquid pump, circulation supply
Heating Method	Infrard heating lamp
Motor Power	90W
Power Supply	AC 110V-240V The current is 50Hz or 60Hz
Machine Dimension	(L*W*H): 2630*930*1050mm
Machine Weight	450kg
Package	1 pc of wooden case
Packing Size	2760*1100*1230mm
Gross Weight 5	50kg

